

# TURNKEY SOLUTIONS FOR NONALCOHOLIC CIDER

Schmidt<sup>®</sup> SIGMA**TEC** Dealcoholization System

# Health Trends and Millennials Driving Demand for Zero-Alcohol Beverages

# API's SIGMATEC Technology Delivers 0.0% Alcohol Beverages and Superior Taste

In recent years, nonalcoholic beverages have been growing in popularity. Today's consumers are seeking healthier options as evidenced by the significant decline of soda consumption due to its high sugar content and link to obesity. Bottled water and juice have become more popular options, particularly among millennials, and this group is driving the sales of no- and low-alcohol beverages as well. Statistics from the 2015 National Survey on Drug Use and Health found that more than 40% of 18- to 25-year-olds reported not having had an alcoholic beverage in the previous month. Nonalcoholic beverages are growing in popularity because it evokes a lifestyle image more sophisticated than that of sodas and juices, fitting the social image that many people want to project about themselves.

Processes designed to dealcoholize beverages have been around for more than 30 years, but consumers did not always accept these products. These lowalcohol products were not the highest quality and had a less than pleasing taste, but better technology and experimentation with ingredients, strongly influenced by craft brewing, has changed that. With the right technology, removing the alcohol no longer means removing the flavor.

API Heat Transfer's Schmidt<sup>®</sup> brand is the technological leader and original patent holder for the vacuum rectification process used to make no-alcohol beverages. This method of dealcoholization better maintains the natural qualities of beverages compared to the traditional process of filtering out the alcohol. API's exclusive SIGMA**TEC** process is the only system capable of producing 0.0% beverages.

The technology can be used to produce beverages with a final alcohol level of 0.0% at a capacity of 2.5 to 4.2 barrels a day.

### SIGMATEC Procedure

Vacuum rectification is the core engineering principle behind SIGMA**TEC** technology. This proprietary dealcoholization process guarantees a very gentle separation of the alcohol from a diverse range of alcoholic products and can be tailored to a customer's product.

For example, consider beer dealcoholization. The first step is decarbonization. Next, the SIGMA**TEC** process removes the alcohol from

the product in its rectification column, the design of which is exclusive to API Heat Transfer, resulting in better flavor and a reduction in alcohol content to below 0.05%. Nearly all competitive processes for beverage dealcoholization end here, but the SIGMA**TEC** process includes further treatment to achieve 0.0% alcohol.

While the product is in the rectification column, alcohol-rich vapors are condensed and cooled at a low temperature in the top of the column. These alcohol-rich vapors can be concentrated up to 85% and stored in a tank in the form of industrial alcohol. The result is a saleable product that can be marketed immediately.

SIGMA**TEC** plants have capacities ranging from 2 to 200 barrels per hour. The technology is environmentally friendly with regard to both water and energy resources. It is also adaptable for various products and formulations.

The technology advances made by API's SIGMATEC modular dealcoholizing plants are becoming increasingly attractive to smaller breweries as well as craft breweries. Today, the SIGMATEC dealcoholization system is used in more than 100 plants around the world.

# **Process Optimization**

From the beginning, API Heat Transfer with its Schmidt<sup>®</sup> brand has successfully established itself as the market leader in innovative and energy efficient equipment, and its engineers continue to develop and optimize the SIGMA**TEC** process. For instance, new dual-stage cooling replaces 80% of glycol with cooling water, thereby reducing operating expenses. For a plant with 100 hl/h, the savings amounts to about 1,000 kW.

Advancements in control technology are enabling operators more flexibility in plant operations. Operators can continuously adjust the performance of their plant via a PLC (Programmable Logic Control) touch screen controller HMI (Human Machine Interface) within a power range of 50-100% without having to make a single mechanical adjustment. A PLC control with ethernet capability and real-time data displays enables operators to monitor performance and avoid premature cleanings, extending the intervals between cleanings and reducing the costs for energy, CIP (Clean-in-Place) products, water and downtime.

Furthermore, automated controls have optimized the maintenance procedures. Startup, cleaning, and shutdown of the plant have improved, saving thousands of liters of water per cleaning cycle.

To learn more about API's exclusive SIGMATEC process or how it can be incorporated into your plant, please email sales@apiheattransfer.com or call (877) 274-4328.

#### Below are the primary advantages of the SIGMATEC process:

- Consistent product quality via continuous running and efficient separation technology
- Ability to decrease alcoholic content to 0.05% or 0.0%, and >20% is possible after adding the alcohol, if desired
- Gentle treatment of the product due to low process temperatures resulting in low thermal stress
- Dealcoholization of beverages minimizes product loss versus concentration
- Patented Aroma Recovery Unit enables aroma components and flavors to be recovered and directed back into the beverage
- Aroma Recovery Unit is a closed steam loop and does not use plant steam, so no boiler chemicals can contaminate the

final product or alter the flavor profile

- Fully automatic operation independent of the plant capacity throughout startup, production, CIP and shutdown
- Low maintenance costs because no releasing agent is required
- Concentration of alcohol up to 85%, which can be marketed as a new product
- Capacity scope of 2-200 hl/h product feed

# Schmidt<sup>®</sup> SIGMATEC Dealcoholization System Capacity: 2 h/l - 200 hl/h

For Breweries, Wineries, And Fruit/Cider Production

### **Areas of Application**

With more than 30 years of experience in dealcoholization, Schmidt<sup>®</sup> SIGMA**TEC** has become the market leader worldwide. With the experience gained in supplying a large number of dealcoholizing plants, our SIGMA**TEC** design has become highly refined.

To date, SIGMA**TEC** systems have been manufactured for a scope of capacity ranging from 2 h/l to 200 hl/h.

Breweries Wheat beer, Pils, Pale Ale, Lager, Dunkel, Stout

Wineries White/Red Wine, Sparkling Wine, Mulled Wine

Fruit/Cider Production Perry, Cider

**Other Industries** Alcoholic Liquids, Extracts

# **Advantages of the Process**

- Dealcoholization under 0.05% alc/vol
- Cost-Effectiveness
  - minimum volume loss
  - alcohol concentration up to 85% alc/vol, hence a valuable, marketable by-product
  - fully automatic operation
  - low energy consumption
  - low maintenance cost
- Careful Handling of Product - low processing temperature
  - short holding time
- Environmentally Beneficial and Advantageous in the Conservation of Resources
- Optional Aroma Recovery
- Optional Dosing of Base Product
- Optional CIP System
- Optional Desulfurization of Grape Juice



# **Technical Versions**

#### **Materials and Specifications**

| Materials of<br>Columns and Tanks: | All Current Stainless Steels                                     |
|------------------------------------|--|
| Column Internals:                  | Exclusively designed, custom structured packing and distribution |
| Column Diameters:                  | Dn 200 to Dn 2,000   |
| Heating System:                    | Direct Steam or Hot Water  |

#### **Capacity Data**

| Feed Capacity:                  | 2 hl/h - 200 hl/h (Beer) |
|---------------------------------|--------------------------|
| Steam Consumption:              | 15 - 18 kg/hl            |
| Cooling Capacity:               | 10 - 12 kw/h             |
| Average Temperature:            | 40 - 80°C                |
| Alcohol Concentration at Inlet: | 0.75 - 15% alc/vol       |
| Final Concentration of Alcohol: | 40 - 85% alc/vol         |







TP Thermal Transfer Products



API Heat Transfer, a family of high-performance brands 🗸

# High-performance heat transfer.

It's who we are and what we do. It's part of our 140-year heritage designing and delivering world-class heat transfer products for nearly every industry. It's bolstered by our worldwide network of manufacturing facilities that provide sales, service, and support. And it's ingrained in a process that has helped customers around the world for nearly a century and a half.

When you work with us, you'll find the performance of our technologies sets the bar for heat transfer products, and our relentless drive to find and create custom heat transfer solutions to meet any industry challenge sets us apart.

# See how our performance can improve yours.

Contact your API Heat Transfer sales rep or visit apiheattransfer.com today.

#### USA

Buffalo Facility 2777 Walden Avenue Buffalo, NY 14225, USA +1.716.684.6700

Iron Ridge Facility 1025 Industrial Road Iron Ridge, WI 53035, USA +1.920.387.4200

#### GERMANY

Bretten Facility Langenmorgen 4 75015 Bretten, Germany +49.7252.53.0

#### **Dortmund Facility**

Breisenbachstrasse 87 44357 Dortmund, Germany +49.231.9920.119

### Franklin Facility

4700 Ironwood Drive Franklin, WI 53132, USA +1.414.761.4500

**Racine Facility** 5215 21st Street Racine, WI 53406, USA +1.262.554.8330

#### **CHINA**

Suzhou Facilities Building 1 156 Qingqiu Street, 3rd District Suzhou Industrial Park Suzhou, Jiangsu 215126, China +86.512.8816.8000

#### **Building 2**

126 Qingqiu Street, 3rd District Suzhou Industrial Park Suzhou, Jiangsu 215126, China +86.512.8816.8000

#### Shanghai

Gubei 1699 Commercial Plaza Room 905-1 1699 Gubei Road Minhang District Shanghai 201103, China +86. 21.5426.2525

