





# **World Leader in Heat Transfer Technology**

API Heat Transfer has grown to become North America's foremost provider of industrial heat transfer equipment. Four plants serving the process and refrigeration industries design and produce a variety of shell and tube, plate and frame, brazed plate and brazed aluminum designs. A worldwide network of qualified representatives and engineers assures the best heat exchanger source for your needs.

## The brazed plate heat exchanger has revolutionized heat transfer.

This heat exchanger combines all the best features of existing heat transfer equipment in to a bold new technology that offers significant benefits.

The critical parameter for any heat exchanger is the amount of surface area it requires to deliver a given amount of heat transfer. The capital cost of heat transfer equipment is commensurate with the amount of surface area, which in turn is directly proportional to the rate of heat transfer.

#### Heavy Duty by Design

When the thermal plates of a brazed plate heat exchanger are assembled together they make contact at thousands of points in each unit. During the brazing process the plates are joined by the braze material at all of these points. This produces a heat exchanger of substantial strength. The benefit is added durability along with higher operating pressures and temperatures.

#### **Product Description**

API Schmidt<sup>®</sup> brazed plate heat exchangers consist of as many as 150 pattern-embossed stainless steel plates. The plates are brazed together, with every second plate turned 180 degrees to create flow channels with two mediums in counter current direction.

The design of the plates creates a high turbulence resulting in outstanding heat transfer. The result is a highly efficient heat exchanger that utilizes all the material in the heat transfer process.

#### Lower Liquid Volume

Since the gap between the heat transfer plates is relatively small, a brazed plate heat exchanger contains only low quantities of process fluids. The benefit to you is reduced cost due to lower volume requirements for often costly refrigerants, coolants or process fluids.

Since the product remains in the heat exchanger for a short period of time, the process can be easily stopped or the temperature can be changed quickly with minimum impact on the product.





# **Experience, Innovation and Reliability.**

#### **Compact with High Efficiency**

The heat transfer plates in a brazed plate heat exchanger are die formed in to a corrugated pattern. When the fluids flow through the heat exchanger across this pattern they are forced in to a highly turbulent flow, which produces high heat transfer coefficients resulting in less surface area required and a smaller heat exchanger.

The result is a heat exchanger that is up to six times smaller than a comparable shell and tube exchanger for the same duty.

#### Low Capital Cost

The brazed plate heat exchanger is assembled from a very small number of machine formed parts. The amount of assembly and manufacturing time is significantly reduced which results in a much lower end user cost.

#### **Highest Level of Quality**

As most of the parts of the brazed plate heat exchanger are machine formed, the highest standard of product quality and performance is easily met.

From delivery of raw materials to installation of the finished product, careful checks are made on quality, compliance with specifications and dimension tolerances.

#### **Flexible Sizes Meet all Needs**

The demands of heat exchanger users vary tremendously from one to another. Some may use very viscous fluids while others may not.

To meet these varying demands API Schmid offers a wide range of sizes of brazed plate heat exchangers. We offer eight different sizes with connections ranging from one half inch up to three inch.

#### **Extremely Lightweight**

The strength of the brazing process allows other components of the heat exchanger to be thinner while still retaining the same amount of pressure. In this manner the unit becomes less expensive, transfers heat better through thinner thermal plates and becomes extremely light and easy to handle.

#### **Superior Corrosion Resistance**

The brazed plate heat exchanger is constructed entirely of corrosion resistant materials. The heat transfer plates and the connections are made from highly resistant 316SS. The standard braze material for joining the unit together is copper but for such applications as ammonia or de-ionized water nickel braze material may be used. The result is many years of dependable service.

#### **Minimal Fouling Effects**

Fouling of the heat transfer surfaces of brazed plate heat exchangers is extraordinarily low. This is a result of good product distribution, constant velocity profile and smooth plate surfaces. The high induced turbulence yields a selfcleaning effect which prevents fouling.



Brazed plate heat exchangers feature corregated stainless steel plates that produce highly turbulent counter-current flow. The result is high heat transfer rates and unmatched efficiency.

# Brazed Plate -vs-Shell & Tube Heat Exchangers



# Take advantage of these features in applications such as:

- Engine lube oil cooling
- Hydraulic oil cooling
- Heat recovery
- Engine jacket cooling
- Refrigerant evaporating
- Refrigerant condensing
- Heat pumps
- Industrial processes
- Boilers
- Hot water converters
- Steam condensers
- District heating
- Steam condensers
- Domestic water heating

#### Manufacturing Capabilities

API Schmidt<sup>®</sup> brazed plate heat exchangers are manufactured in ultra-modern facilities. The brazing ovens feature sophisticated controls that assure even heating at the correct brazing temperature for the materials selected.

Assembly robots stack plates and locate connections correctly. Each finished model is tested to assure leak free performance.



# **API Heat Transfer**

API Schmidt<sup>®</sup> brazed plate heat exchangers consist of as many as 150 pattern embossed stainless steel plates. The plates are brazed together with every other plate turned 180° to create flow channels with two mediums in counter-current direction. The design of the plates creates a high fluid turbulence resulting in outstanding heat transfer rates. The result is a highly efficient heat exchanger that utilizes all of the material in the heat transfer process.



#### **Materials of Construction**

Thermal Plates	316 Stainless Steel
Cover Plates	. 316 Stainless Steel
Connections	316 Stainless Steel
Braze Material	Copper
Optional	Nickel

#### **Operating Conditions**

Maximum	Pressure
---------	----------

Copper Braze	450 Psi
Nickel Braze	230 Psi
Maximum Temperature	365°F
Minimum Temperature	-148°F

#### **Connection Types**

Standard	NPT Soldering
Optional	SAE type Flanged

#### Capacities

Model	GPM
SB1	
SB2	
SB3	
SB22	20
SB3	50
SB4	50
SB5	50
SB7	175
SB8	385

#### Maximum Connection Size

Model	Size
SB1	3/4"
SB2	1"
SB3	1"
SB22	1"
SB3	1"
SB4	1"
SB5	1"
SB7	2"
SB8	3"

Approvals



ASME Code Stamp available on selected models

# Schmidt<sup>®</sup> Brazed Plate Heat Exchanger Dimensions





API Model Type		D	imensions i	n Inches		Max Number	Surface per	MaxFlow	Weight Empty
	A	В	C	D	F	of Plates	Plate (sq.ft.)	(gpm)	(lbs)
SB1	2.88	8	1.63	6.56	.013+ (.09 x N)	30	.13	20	1.65+(.11xN)
SB2	3.5	9.06	1.69	7.19	.013+ (.09 x N)	50	.15	20	2.42+ (.13xN)
SB22	3.5	12.8	1.69	10.98	.013+ (.09 x N)	30	.24	20	3.14+(.18xN)
SB3	4.88	6.73	2.88	4.72	.013+ (.09 x N)	50	.16	50	2.64+(.13xN)
SB4	4.88	13.07	2.88	11.06	.013+ (.09 x N)	100	.32	50	3.52+(.26xN)
SB5	4.88	20.83	2.88	18.81	.013+ (.09 x N)	100	.53	50	4.4+(.53xN)
SB7	10.59	20.83	7.88	18.13	.013+ (.09 x N)	150	1.46	175	12.1+(1.32xN)
SB8	10.59	20.83	6.34	16.57	.013+ (.09 x N)	150	1.29	385	12.1+(1.32xN)

API Model Type		Dim	ensions in l	Villimeters		Max Number	Surface per	MaxFlow	Weight Empty
	A	В	C	D	F	of Plates	Plate (sq.m.)	(m³/h)	(Kg)
SB1	73	203	40	170	7+(2.3xN)	30	.012	4.5	.75+(.05xN)
SB2	89	230	43	182	7+(2.3xN)	50	.014	4.5	1.3+(.08xN)
SB22	89	325	43	279	7+(2.3xN)	30	.022	4.5	1.3+(.08xn)
SB3	124	171	73	120	7+(2.3xN)	50	.015	11	1.2+(.06xN)
SB4	124	332	73	281	7+(2.3xN)	100	.03	11	1.6+(.12xN)
SB5	124	529	73	478	7+(2.3xN)	100	.049	11	2.0+(.24xN)
SB7	269	529	200	460	7+(2.3xN)	150	.136	40	5.5+(.6xN)
SB8	269	529	161	421	7+(2.3xN)	150	.120	88	5.5+(.6xN)

## **Brazed Plate Evaporators and Condensers**

API Schmidt<sup>®</sup> brazed plate heat exchangers are highly efficient in refrigerant service. Their small size, low refrigerant charge and superior efficiency makes them ideal as evaporators, condensers and subcoolers. Standard models are stocked to 30 tons of capacity. Special order models are available for virtually any duty.

Brazed plate heat exchangers are available with copper brazing materials for use with halocarbon based refrigerants such as R-22 and R-404a. Models with nickel brazing materials are available for use with ammonia.

Evaporator models above a certain number of plates include internal refrigerant distribution features to assure proper distribution of refrigerant gas and maximize the efficiency of the unit. This also assures proper superheat.

Their compact size makes them easy to package into small tonnage refrigeration systems, saving time and money.

## **Evaporator and Condenser Piping**



EVAPORATORS								CONDENS	SERS		
Model Number	Nominal Tons	Ref. Conn.	Water Conn.	Depth In.	Weight Lbs.	Model Number	Nominal Tons	Ref. Conn.	Water Conn.	Depth In.	Weight Lbs.
SB22-8	.5	5/8	7/8	1.2	4	SB22-8	.5	5/8	7/8	1.2	4
SB22-10	0.8	5/8	7/8	1.4	5	SB22-10	0.8	5/8	7/8	1.4	5
SB22-14	1.0	5/8	7/8	1.8	5	SB22-14	1.0	5/8	7/8	1.8	5
SB22-20	1.5	5/8	1-1/4	2.4	6	SB22-20	1.0	5/8	7/8	2.4	6
SB22-20	2.0	5/8	7/8	2.4	6	SB22-24	2.0	5/8	7/8	2.8	7
SB22-24	2.5	5/8	7/8	2.8	7	SB22-30	2.5	5/8	7/8	3.3	8
SB4-20	3.0	7/8	1-1/4	2.4	9	SB4-24	2.5	7/8	1-1/4	2.8	10
SB4-24	3.5	7/8	1-1/4	2.8	10	SB4-24	3.5	7/8	1-1/4	2.8	10
SB5-20	4.0	7/8	1-3/8	2.4	15	SB5-20	4.0	7/8	1-3/8	2.4	15
SB5-24	5.0	7/8	1-3/8	2.8	17	SB5-20	5.0	7/8	1-3/8	2.4	15
SB5-30	6.0	1-3/8	1-3/8	3.3	20	SB5-24	6.0	7/8	1-3/8	2.8	17
SB5-34	7.5	1-3/8	1-3/8	3.7	22	SB5-30	7.5	1-3/8	1-3/8	3.3	20
SB5-44	10.0	1-3/8	1-3/8	4.6	28	SB5-40	10.0	1-3/8	1-3/8	4.3	26
SB5D-60	12.5	1-3/8	1-3/8	6.1	36	SB5-50	12.5	1-3/8	1-3/8	4.6	31
SB5D-70	15.0	1-3/8	1-3/8	7.1	41	SB5-70	15.0	1-3/8	1-3/8	7.1	41
SB5D-100	20.0	1-3/8	1-3/8	9.9	57	SB5-80	20.0	1-3/8	1-3/8	8.0	47
SB7M-50	25.0	2-1/8	2-1/8	5.2	78	SB5-100	25.0	1-3/8	1-3/8	9.9	57
SB7M-60	30.0	2-1/8	2-1/8	6.1	91	SB7M-50	30.0	2-1/8	2-1/8	5.2	78

Evaporator performance based on cooling water at 2.4 GPM per ton from 54°F to 44°F in R-22 service at 35°F SST and 6°F superheat. Condenser performance based on R-22 service at 105°F condensing temperature and using 3 GPM per ton of cooling water at 85°F.







TP Thermal Transfer Products



API Heat Transfer, a family of high-performance brands 🗸

## High-performance heat transfer.

It's who we are and what we do. It's part of our 140-year heritage designing and delivering world-class heat transfer products for nearly every industry. It's bolstered by our worldwide network of manufacturing facilities that provide sales, service, and support. And it's ingrained in a process that has helped customers around the world for nearly a century and a half.

When you work with us, you'll find the performance of our technologies sets the bar for heat transfer products, and our relentless drive to find and create custom heat transfer solutions to meet any industry challenge sets us apart.

## See how our performance can improve yours.

Contact your API Heat Transfer sales rep or visit apiheattransfer.com today.

#### USA

Buffalo Facility 2777 Walden Avenue Buffalo, NY 14225, USA +1.716.684.6700

Iron Ridge Facility 1025 Industrial Road Iron Ridge, WI 53035, USA +1.920.387.4200

#### GERMANY

Bretten Facility Langenmorgen 4 75015 Bretten, Germany +49.7252.53.0

#### **Dortmund Facility**

Breisenbachstrasse 87 44357 Dortmund, Germany +49.231.9920.119

### Franklin Facility

4700 Ironwood Drive Franklin, WI 53132, USA +1.414.761.4500

**Racine Facility** 5215 21st Street Racine, WI 53406, USA +1.262.554.8330

#### **CHINA**

Suzhou Facilities Building 1 156 Qingqiu Street, 3rd District Suzhou Industrial Park Suzhou, Jiangsu 215126, China +86.512.8816.8000

#### **Building 2**

126 Qingqiu Street, 3rd District Suzhou Industrial Park Suzhou, Jiangsu 215126, China +86.512.8816.8000

#### Shanghai

Gubei 1699 Commercial Plaza Room 905-1 1699 Gubei Road Minhang District Shanghai 201103, China +86. 21.5426.2525

