

SCHMIDT® SIGMASHELL



Schmidt[®] SIGMASHELL All-Welded Plate & Shell Heat Exchanger

Our SIGMASHELL all-welded plate and shell heat exchangers offer a unique combination of the ruggedness and high-pressure capability of a shell and tube with the compactness and high thermal efficiency of a plate heat exchanger.

Features:

- Cylindrical shell design to handle high-pressure applications
- High thermal efficiency and surface density
- Fishbone corrugation for superior high and low heat transfer characteristics
- Shell construction flexibility
- All-welded for a gasket-free design
- Accessible to one or two sides for easy inspection and cleaning
- Multi-pass possible for shell and plate side
- Thermal plates available in stainless steel, titanium and Hastelloy[®]

Benefits:

- Quick start-up time
- Very resistant to thermal shock
- Ideal for high temperature and pressure applications
 - Operating pressures from vacuum to 150 barg = 2176 psig
 - Operating temperatures from -200° C = -328° F to 500° C = 1022° F
 - Viscosities up to 8,000 mPas
- Compact, lightweight design to minimize volumetric hold-up
- Easy to maintain
- Small footprint





Quality Construction Ensures Superior Performance and Reliability

Our Schmidt[®] SIGMASHELL is a laser-welded design, providing greater cross-sectional weld area at minimum heat input and resulting in little change to material microstructure. Its smaller weld pool volume reduces the risk of sink holes and pores during solidification to prevent leaks.

Our laser welding is more capable and stronger against failures along the circumferential weld seams. These advantages result in plate packs with a higher degree of integrity and a longer life cycle.

Dimensions

	SP 50	SP 100	SP 150	SP 200	SP 300
S1, S2	3/4" - 4"	1" - 10"	2" - 14"	2" - 28"	2" - 24"
P1, P2	2"	4"	6"	8"	12"
Ø [mm]	360	610	890	1,100	1,400
L [mm]	from 150 (depending on number of plates and design pressure) to 2,400				
Area [m ²]	1.5 to 30	max 100	max 320	max 500	max 700

Wide Range of Industry Applications:

- Chemical
- Petrochemical
- Pharmaceutical
- Power
- Alternate Energy
- Steel Mills



Construction and Function



Plate Patterns

H-Plate

Small angle
Higher transfer efficiency

L-Plate

- Wide angle
 - Less pressure drop

G-Plate

Deeper corrugation depth and bigger channel width
Bigger cross section



H-Plate and L-Plate



G-Plate





Compact Design

- More heat transfer surface with less space
 - Smaller footprint
- Even distribution of the stress
 - Minimized risk of the stress cracking cylindrical shell
 - Optimal design for pressure vessel
 - Small thickness, low weight



Accessible Plate Package

Inspection and cleaning up the plate package by opening the shell



Plate Package

- Laser-welded round plate pack
- Latest technology for shell & plate heat exchangers
- Huge joining cross section
- Minimal heat input
- Small heat-affected zone, small change in the material structure
 - Round laser-welded plate package shows an improved safety against leakage and less corrosion potential compared to other shell & plate heat exchangers
 - Higher design pressure can be achieved





Cleaning of Heat Exchangers

When cleaning heat exchanger plates, fouling layers are removed from the heat transfer surface, i.e., deposits formed during operation, which hinder the heat transfer. During operation any combination of the following kinds of fouling are possible:

- Crystallisation fouling
- Particle fouling (also sedimentating fouling)
- Corrosion fouling
- Biological fouling

For welded plate heat exchangers basically two cleaning methods can be used:

Chemical cleaning

Depending on the design of the Plate & Shell heat exchanger, chemical cleaning can be differentiated in:

- CIP cleaning (Cleaning in Place), for openable and fully welded units
- Immersion bath cleaning

The immersion bath cleaning is only applicable to plate packages in openable Plate & Shell heat exchangers.

Mechanical cleaning

Depending on the design and installation of the Plate & Shell heat exchanger, mechanical cleaning methods can be differentiated as:

- Back flushing
- High-pressure cleaning

The high-pressure cleaning is only applicable to openable units. The disassembled plate pack is cleaned by steam or high-pressure water jet (800 to 1000 bar).









TP Thermal Transfer Products



API Heat Transfer, a family of high-performance brands 🗸

High-performance heat transfer.

It's who we are and what we do. It's part of our 140-year heritage designing and delivering world-class heat transfer products for nearly every industry. It's bolstered by our worldwide network of manufacturing facilities that provide sales, service, and support. And it's ingrained in a process that has helped customers around the world for nearly a century and a half.

When you work with us, you'll find the performance of our technologies sets the bar for heat transfer products, and our relentless drive to find and create custom heat transfer solutions to meet any industry challenge sets us apart.

See how our performance can improve yours.

Contact your API Heat Transfer sales rep or visit apiheattransfer.com today.

USA

Buffalo Facility 2777 Walden Avenue Buffalo, NY 14225, USA +1.716.684.6700

Iron Ridge Facility 1025 Industrial Road Iron Ridge, WI 53035, USA +1.920.387.4200

GERMANY

Bretten Facility Langenmorgen 4 75015 Bretten, Germany +49.7252.53.0

Dortmund Facility

Breisenbachstrasse 87 44357 Dortmund, Germany +49.231.9920.119

Franklin Facility

4700 Ironwood Drive Franklin, WI 53132, USA +1.414.761.4500

Racine Facility 5215 21st Street Racine, WI 53406, USA +1.262.554.8330

CHINA

Suzhou Facilities Building 1 156 Qingqiu Street, 3rd District Suzhou Industrial Park Suzhou, Jiangsu 215126, China +86.512.8816.8000

Building 2

126 Qingqiu Street, 3rd District Suzhou Industrial Park Suzhou, Jiangsu 215126, China +86.512.8816.8000

Shanghai

Gubei 1699 Commercial Plaza Room 905-1 1699 Gubei Road Minhang District Shanghai 201103, China +86. 21.5426.2525

